



➤ ***BLACK ARROW***

TBR
CATALOGUE



BA71

➤ **Deliver a smooth and consistent wear**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPa)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
12R22.5	18	152/149	L	21.5	9	3550	3250	930	1085	300

BA72

➤ **Exceptional road holding and passing capability**



SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPa)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
11R22.5	16	146/143	L	20.0	8.25	3000	2725	930	1054	279
11R22.5	18	149/146	L	20.0	8.25	3250	3000	930	1054	279

➤ **BLACK ARROW**



BA73

➤ **Highly effective traction and braking performance**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPa)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
11.00R20	18	152/149	K	19.0	8.0	3550	3250	930	1085	293
12.00R20	20	156/153	K	19.0	8.5	4000	3650	900	1125	315

BA76

➤ **Prevent stone retention and provide self cleaning capability**



SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPa)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
11.00R20	18	152/149	K	18.0	8.0	3550	3250	930	1085	293
12.00R20	20	156/153	K	18.5	8.5	4000	3650	900	1125	315

➤ **BLACK ARROW**



BA77

➤ **sound bearing, braking and driving capability**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPA)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
11R22.5	16	146/143	L	20.0	8.25	3000	3725	930	1054	279
11R22.5	18	149/146	L	20.0	8.25	3250	3000	930	1054	279

BA78



➤ **Improve traction, driving and braking performance**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPA)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
11.00R20	18	152/149	J	24.0	8.0	3550	3250	930	1085	293
12.00R20	20	156/153	J	24.5	8.5	4000	3650	900	1125	315

➤ **BLACK ARROW**



BA79

➤ **Enhance stability and resistance to abrasion**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPA)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
11.00R20	18	152/149	J	24.0	8	3550	3250	930	1085	293
12.00R20	20	156/153	J	24.5	8.5	4000	3650	900	1125	315

BA81

➤ **Sound water-evacuation and skidding-resistance capability**



SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPA)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
11R22.5	16	146/143	L	15.5	8.25	3000	2725	830	1054	279
11R22.5	18	149/146	L	15.5	8.25	3250	3000	930	1054	279
11.00R20	18	152/149	K	17	8	3550	3250	930	1085	293
12.00R20	20	156/153	K	17.5	8.5	4000	3650	900	1125	315

➤ **BLACK ARROW**



BA82

➤ **Provide outstanding wet performance**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPA)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
12R22.5	18	152/149	L	17.5	9	3550	3250	930	1085	300
11.00R20	18	152/149	K	17.0	8.0	3550	3250	930	1085	293
12.00R20	20	156/153	K	17.5	8.5	4000	3650	900	1125	315

BA83

➤ **Excellent traction and maneuverability**



SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPA)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
12R22.5	18	152/149	M	15.0	9	3550	3250	930	1085	300

➤ **BLACK ARROW**



BA92

- **Provide excellent heat dissipation and improved regular wear with lower resistance**

SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPa)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
12R22.5	18	152/149	L	15.0	9	3550	3250	930	1085	300

BA93

- **With excellent anti-side-skid character, low rolling resistance**



SIZE	PR	LOAD INDEX	SPEED SYMBOL	TREAD DEPTH	STANDARD RIM	SINGLE	DUAL	PRESSURE (kPa)	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)
11R22.5	16	146/143	L	15.0	8.25	3000	2725	830	1054	279
11R22.5	18	149/146	L	15.0	8.25	3250	3000	930	1054	279