



 FORTIRE
TRUCK & BUS TIRES CATALOG





FORTIRE
CM-1003

- ※ Sound water-evacuation and skidding-resistance capability
- ※ Soundly resistance irregular wear

SIZE	Load Index	Speed Symbols	Depth (mm)	Standard Rim	Max Load and Inflated Pressure				Section Width (mm)	Overall Diameter (mm)	Weight (kg)
					Dual		Single				
					kg	kpa	kg	kpa			
11R22.5	146/143	M	15.0	7.50,8.25	2725	830	3000	830	279	1054	51.80
11R24.5	149/146	M	15.0	7.50,8.25	3000	830	3250	830	279	1104	55.60
295/75R22.5	146/143	M	15.0	8.25, 9.00	3000	830	2725	830	298	1014	50.65



FORTIRE
CM-1023

- ※ Suitable for good road surface application
- ※ With excellent anti-side-skid character,low rolling resistance
- ※ Low heat generating,excellent high-speed driving character

SIZE	Load Index	Speed Symbols	Depth (mm)	Standard Rim	Max Load and Inflated Pressure				Section Width (mm)	Overall Diameter (mm)	Weight (kg)
					Dual		Single				
					kg	kpa	kg	kpa			
11R22.5	146/143	L	21.0	7.50,8.25	2725	930	3000	930	279	1065	54.60
11R24.5	149/146	L	21.0	7.50,8.25	3000	830	3250	830	279	1116	58.60
295/75R22.5	146/143	L	21.0	8.25, 9.00	3000	830	2725	830	298	1020	52.80



FORTIRE
CM-1013

- ※ Sounds bearing,braking and driving capability

SIZE	Load Index	Speed Symbols	Depth (mm)	Standard Rim	Max Load and Inflated Pressure				Section Width (mm)	Overall Diameter (mm)	Weight (kg)
					Dual		Single				
					kg	kpa	kg	kpa			
11R22.5	146/143	M	15.0	7.50,8.25	2725	830	3000	830	279	1054	51.80
11R24.5	149/146	M	15.0	7.50,8.25	3000	830	3250	830	279	1104	55.60



FORTIRE
CM-1033

- ※ Suitable to transport on asphaltroad or other bad roadcondition
- ※ Tyres with pattern have powerful grip ability, excellent traction character

SIZE	Load Index	Speed Symbols	Depth (mm)	Standard Rim	Max Load and Inflated Pressure				Section Width (mm)	Overall Diameter (mm)	Weight (kg)
					Dual		Single				
					kg	kpa	kg	kpa			
11R22.5	146/143	J	23.0	8.25	2750	830	3000	830	279	1065	56.50
11R24.5	149/146	J	23.0	8.25	3000	830	3250	830	279	1116	69.50